

# **MDR-1200**

### 8" MIDRANGE LOUD SPEAKER WITH DRIVER

MIDRANGE SPECIFICATIONS:

8" MIDRANGE WTTH DRIVER LOUDSPEAKER

HIGH STRENGTH AIUMINUM BASKET

2.5" HIGH TEMPERTURE CCAW VOICE COIL

600 WATTS RMS POWER

1200 WATTS MAX POWER

SENSITIVITY 93 dB

**IMPEDANCE: 8 OHMS** 

PROGRESSIVE COOLING SYSTEM


**DRIVER SPECIFICATIONS:** 

44MM HIGH PERFORMANCE DIAPHRAGM


SENSITIVITY 101 dB

**IMPEDANCE: 8 OHMS** 

PROGRESSIVE COOLING SYSTEM



Midrange SPL & Freq



Driver SPL & Freq









8" MIDRANGE

LOUD SPEAKER WITH DRIVER



# ((YTZ)) Hudio





# **MDR-1200**

### **8" MIDRANGE LOUD SPEAKER WITH DRIVER**

S	oecifica	tions:
_		

Nominal Diameter	. 8"
Nominal Impedance	8 ohms
MAX Power Handing	1200W
RMS Power Handing	600W
Sensitivity (1w/1m)	93dB
Frequency Response	-17.2KHz

## Midrange Motor:

•	
Voice Coil Diameter	2.5"/63.5 mm
Voice Coil Former Material	Glass Fiber
Winding Material	CCAW
Cone Material	Paper
Surround Material	
Basket Material	
Magnet Material	Ferrite
Magnets Size	158*20mm

### Thiele & Small Parameters:

Equivalent Volume	Vas 23.323 L
Excursion	X-max 9.2 mm
Free Air Resonance	Fs 72.17 Hz
Mechanical Factor	Qms 10.313
Electrical Factor	Qes 0.8277
Total Factor	Qts
Dc Resistance	Re 5.2 ohms

### Measurements

Overall Diameter	8.22"/209 mm
Front Mount Baffle Cutout	.7.33"/186.2 mm
Mounting Depth	4.75"/120.8 mm
Overall Depth	5.12"/130 mm
Motor Diameter	6.22"/158mm

